

ELLIOTT

9000

Volume 2: PROGRAMMING INFORMATION
Part 2: PROGRAM DESCRIPTIONS
Section 17: QDASQRT (B. 106A)

Contents

	Page
Chapter 1: INTRODUCTION	
1.1 Purpose	1
1.2 Form of Distribution	1
1.3 Method of Use	1
1.4 Accuracy	1
Chapter 2: FUNCTIONS	
2.1 Notation	2
2.2 Format	2
2.3 Entry and Exit	2
2.4 Identifiers	2
Chapter 3: ERROR INDICATIONS	3
Chapter 4: METHOD USED	
4.1 Special Cases	3
4.2 General Cases	3
Chapter 5: TIME TAKEN	
5.1 Special Cases	4
5.2 General Cases	4
Chapter 6: STORE USED	4

1111111111

0000000000

Printed in England by
Engineering Unit, English Electric Computers Ltd.

Chapter 1: INTRODUCTION

1.1 Purpose

To calculate, as a double-length fraction, the square root of a double-length fraction, a.

1.2 Form of Distribution

The program is distributed as a SIR mnemonic tape.

1.3 Method of Use

The routine is assembled as a block of the user's program and entered as a sub-routine. It can be run at any program level and in any store module.

When QDASQRT is used, QDLA must also be held in store.

1.4 Accuracy

The maximum error is 3×2^{-34} . (0.2×10^{-9})

Chapter 2: FUNCTIONS

2.1 Notation

$x(m.s)$ = most significant half of x
 $x(l.s)$ = least significant half of x

2.2 Format

A double-length fraction, x , is held in two consecutive locations, X and $X+1$;

Bit 18 of $X+1$ must be zero;
Bit 18 of X gives the sign of x ;
Bits 17-1 of X give the 17 most significant bits of x .
Bits 17-1 of $X+1$ give the least significant bits of x .

Negative number representation is by the usual 2's complement notation.

2.3 Entry and Exit

A double-length number is held in two consecutive locations: only the first location is given below.

Entry

place a in $QDASQRT+44$
and enter $11QDASQRT$
 $8QDASQRT+1$

Exit \sqrt{a} in $QDASQRT+46$

N. B. The instruction pair

$11 QDASQRT$
 $8 QDASQRT+1$

must not be part of a pseudo-program interpreted by $QDLA$.

2.4 Identifiers

$QDASQRT$ must be declared as a global identifier in all blocks of a SIR program which refer to it.

Chapter 3: ERROR INDICATION

If $a < 0$
then 0000.010 is output continuously.

Chapter 4: METHOD USED

QDASQRT uses QDLA to interpret some of the double-length calculations.

4.1 Special Cases

QDASQRT first tests for special values of the operand. If a is equal to any of these the appropriate answer is read and exit made immediately.

Special values are:

$a = 0$
 $a = 1 - 2^{-34}$

In these cases \sqrt{a} is taken as a

4.2 General Cases

Otherwise QDASQRT uses an iterative formula

taking $n = 0, 1, 2, 3, \dots$

and $x_0 = 1 - 2^{-34}$

$x_{n+1} = \frac{1}{2}(x_n + a/x_n)$

When $x_{n+1} \geq x_n$

then x_n is the best approximation to \sqrt{a} .

Chapter 5: TIME TAKEN

5.1 Special Cases

a = 0 570 microseconds.

a = $1-2^{-34}$ 1053 microseconds.

5.2 General Cases

Approximate time taken is

$$3.0 + 12.5 n \text{ milliseconds}$$

where n is the number of iterations necessary.

Chapter 6: STORE USED

QDASQRT uses 52 consecutive locations.